

- **Deluxe heavy duty patient tray delivery s/s cart**
- **Single section non-insulated, easy to maneuver**

This deluxe cart offers excellent mobility in transporting 15"x20" meal trays for room service application.

Construction:

This cart is provided with all welded heavy duty s/s construction. Deck is 14 ga. s/s with all edges turned down & corners welded. Uprights are 2"x1"x14 ga. s/s formed channels welded to deck and top. Sides and back are 18 ga. s/s and top is double panels of 20 ga. s/s. Door is 18 ga. s/s brake formed with hemmed sides, pan type construction, reinforced with 1" square s/s tubing. Door swings 270° on heavy duty 12 ga. s/s hinges rotating on 3/8" Ø s/s pins. The sides are reinforced at top with 1" square s/s tubing. 18 ga. s/s slides are welded to a frame which is easily removable for cleaning. A s/s gravity latch provides for easy opening and closing of door. 5" polyurethane swivel casters are standard. The slides are spaced on 4 7/8" spacing to carry 8 trays (15"x20") single end loaded. Other spacings are available. Cart has polished finish on exterior.



Model 2200-1-HD-1508
Shown with optional package "DX"

Model Number	Tray Size (inches)	Tray Capacity	Tray Spacing (Inches)	*O.A. Dimensions (Inches)			Weight (Pounds)
				W	D	H	
2200-1-HD-1508	15x20	8	4 7/8	22	25	48 3/4	190



***Note:** Add 2" to O.A. width & depth if ordered with optional corner or wrap around bumper. O.A. height will increase by 1 1/4" if ordered with optional 6" balloon casters, and an additional 1 1/2" to 3" if ordered with optional top rail.

The following options are available.

1. Optional Package "DX":

- | | |
|--|----------------------------------|
| A. Swing door catch | D. One push handle |
| B. Wrap around bumper | E. 3 sided top rail (angle type) |
| C. 6" Balloon non marking casters (in lieu of 5" poly) | F. Cart drain hole |
- Note:** These options can also be individually ordered instead of complete package.

2. Other Available Options:

- | | |
|---|---|
| A. 1" square or round tubing type 3 or 4 sided top rail instead of angle slide type rail. | E. Lockable latch |
| B. Corner bumpers instead of wrap around bumper. | F. Universal step angle slides to accommodate both 14"x18" or 15"x20" trays |
| C. Wheel brakes. | G. Fixed slides (non removable rack) |
| D. Pass thru' doors | H. 5" cushion rubber casters (in lieu of 5" poly) |
- Note:** Cabinets for trays other than 15"x20" and for different capacity or spacing are also available. Consult factory.

STAINLESS STEEL & ALUMINUM PATIENT TRAY DELIVERY/ ROOM SERVICE CARTS

390-A Meyer Circle, Corona, California 92879-1078

Phone (951) 340-3419

Fax (951) 340-2716

- Choice of s/s or aluminum patient tray delivery carts.
- Single section, non-insulated, easy to maneuver.
- Choice of single end loading or double side loading for 15"x20" trays.

These carts provide exceptional value and are extremely well built to provide years of service. Slides are fixed and require little or no maintenance. S/S carts use combination of heavy gauge s/s deck & 18 & 20 ga. sides, tops, slides, back & doors. Aluminum carts use 0.125" thick deck & uprights with back, side panels and door ranging in thickness from 0.063" thru" 0.080". S/S hinges provide 270 ° door swing. 5" Polyurethane casters are standard.



S/S Model 2200-1-F-1507
Shown with optional corner bumpers

One Tray / Pair of Slides (Single End Loaded)

Type	Model Number	Tray Size	Tray Capacity	Tray Spacing	* O.A. Dimensions (Inches)			Weight (Pounds)
					W	D	H	
S/S	2200-1-F-1507	15x20	7	4 3/4	19 7/8	25	42 1/8	135
Aluminum	9200-1-F-1507	15x20	7	5 1/16	19 7/8	25	44 7/8	104
Aluminum	9200-1-F-1508	15x20	8	5 1/16	19 7/8	25	49 7/8	112

Two Trays / Pair of Slides (Double Side Loaded)

Type	Model Number	Tray Size	Tray Capacity	Tray Spacing	* O.A. Dimensions (Inches)			Weight (Pounds)
					W	D	H	
S/S	2200-1-F-1514	15x20	14	4 3/4	24 1/4	35 1/8	42 1/8	230
Aluminum	9200-1-F-1514	15x20	14	5 1/16	24 1/4	35 1/8	44 7/8	135
Aluminum	9200-1-F-1516	15x20	16	5 1/16	24 1/4	35 1/8	49 7/8	149

*Note: Add 2" to O.A. width & depth if ordered with optional corner or wrap around bumper. O.A. height will increase by 1 1/4" if ordered with optional 6" balloon casters, and an additional 1 1/2" to 3" if ordered with optional top rail.



Options:

- | | |
|------------------------------|---|
| A. Corner bumpers | G. 6" Balloon casters |
| B. Wrap around bumper | H. 3 sided top rail (angle or tubular type) |
| C. Swing door catch | I. Drain hole |
| D. Push handle | J. Removable rack (s/s cart) |
| E. 5" cushion rubber casters | K. Wheel brakes |
| F. Pass thru' doors | L. Lockable latch |

Note: Cabinets for trays other than 15"x20" are also available. Optional vinyl is also available. Refer to catalog page B-7 for taller carts for various tray sizes & spacings.

Better food service equipment — standard models and custom designs.

B-28