

Ultra value transport & storage cabinets for bun pans, non-insulated aluminum

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

Ultra Value transport & storage cabinets, for bun pans, non-insulated, aluminum

- Designed for 18"x26" bun pans.
- All welded aluminum construction.
- 1/8" thick channel uprites.
- 0.080" thick back, 0.070" thick top & approx. 1/8" thick formed door.
- 14 ga. s/s gravity latch.
- Reinforced deck.
- 3 Sets of hinges (270° door swing). for larger cabinets.

- Interlocking extruded side panels with guides spaced on 1½" centers with ½" ledges.
- ½" Dia. Horizontal tie rod in the front for extra rigidity.
- Pans are lip loaded.
- 5" Polyurethane casters, 2 with brakes.
- Door hold open slide catch.



Model Number	No. of Runners	Pan Size	Pan Spacing	O.A. Dimensions (Inches)	Weight (Pounds)
		(Inches)	(Inches)	WxDxH	
9220-BL-1839	39	18 x 26	1½	20½x27¼x67	120
9220-BL-1816	16	18 x 26	1½	20½x27¼x31	84



Options: Options:

Corner bumpers (set of 4) Prison package

Wrap around bumper (includes 5 sets of hinges, extra interior bracing, 6" poly casters, pad lock hole in door & tamper proof screws)

Wheel brakes (pair)

Door tag holder

package 9220-BL-1839

Additional Correctional Options: (for 9220-BL-1839)

Options:	Options:
Reinforced top	30" long lockable latch
Reinforced 2 vertical sides	48" long lockable latch
Reinforced deck	6" x 2" H.D. poly casters
Reinforced door	6" balloon casters



9220-BL-1816

Better food service equipment - standard models and custom designs.