

Hot insulated double door cabinets for smaller compartment trays for correctional facilities

390-A Meyer Circle • Corona, CA 92879-1078 • Phone (951) 340-3419 • Fax (951) 340-2716 • www.sammonsequipment.com

- Fully insulated hot s/s cabinets.
- Bottom mounted heating unit with 1600W heating.
- 2 different styles offered. (Choice of trays on 3" centers or stacked)
- 6" casters, push handle & perimeter bumper are standard.
- Heavy duty reinforced correctional hinges.

These hot cabinets are furnished with 1 1/2" fiberglass insulation and are offered in two styles, one with removable rack with fixed slides spaced on 3" centers and the other with removable flat square tubing shelves for stacking trays. Cabinets roll easily on 6" casters, 2 with brakes. The bottom mounted heating unit is easily removable (non-removable optional) & provides the necessary gentle & forced air circulation with thermostatically controlled temperature.

Outer body, door & top are made of 20 ga. (18 ga. optional) polished stainless steel for strength & durability. Inners are made of 22 ga s/s. Push handle, perimeter bumper, tamper resistant fasteners, heavy duty reinforced correctional hinges, latches and dial thermometer are standard.

HE-1600 Heating Unit:

1600 W heating coil, 1,675W total, 13.96 amps at 120 VAC 60 HZ single phase furnished with 15 amps, 8ft. long cord with 3 prong Nema 5-15 P grounding plug, off-on switch, 75W blower, thermostat and pilot lights. Unit has over 4 quarts capacity water reservoir. Blower and heating coils are thermally protected. Optional 220-240V available.

Optional HE-2000 heating unit with 2000W heating coil and 20 amps cord and 5-20P plug for *20 amps service is also available. Consult factory.

*For Canadian application HE-2000 and HE-1600 are furnished with 30 amps/20amps cord and plug respectively.



STYLE "A"
(shown with optional left section ambient)

STYLE "A": Slides are spaced on 3" centers (Double sets of rack in each section)

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2285-HIN-4-910-112	9 x 10 1/2 x 2 1/2	3	112	31 1/2 x 58 3/4 x 64 3/8	590
2285-HIN-4-910-96	9 x 10 1/2 x 2 1/2	3	96	31 1/2 x 58 3/4 x 58 3/8	565
2285-HIN-4-910-80	9 x 10 1/2 x 2 1/2	3	80	31 1/2 x 58 3/4 x 52 3/8	530
2285-HIN-4-0608-168	6 3/8 x 8 1/2 x 2 1/8	3	168	31 1/2 x 57 1/4 x 64 3/8	570
2285-HIN-4-0608-144	6 3/8 x 8 1/2 x 2 1/8	3	144	31 1/2 x 57 1/4 x 58 3/8	536
2285-HIN-4-0608-120	6 3/8 x 8 1/2 x 2 1/8	3	120	31 1/2 x 57 1/4 x 52 3/8	510

STYLE "B": Trays are to be stacked. Cabinet furnished without slides, but supplied with removable tubular shelves for stacking trays.

Model Number	Tray Size (Inches)	Tray Spacing (Inches)	Tray Capacity	O.A. Dimensions (Inches) D x W x H	Weight (Pounds)
2285-HIN-2-ST-910-112	9 x 10 1/2 x 2 1/2	Stacked	112	31 1/2 x 58 3/4 x 64 3/8	510
2285-HIN-2-ST-910-96	9 x 10 1/2 x 2 1/2	Stacked	96	31 1/2 x 58 3/4 x 58 3/8	486
2285-HIN-2-ST-910-80	9 x 10 1/2 x 2 1/2	Stacked	80	31 1/2 x 58 3/4 x 52 3/8	440
2285-HIN-2-ST-0608-192	6 3/8 x 8 1/2 x 2 1/8	Stacked	192	31 1/2 x 57 1/4 x 64 3/8	500
2285-HIN-2-ST-0608-168	6 3/8 x 8 1/2 x 2 1/8	Stacked	168	31 1/2 x 57 1/4 x 58 3/8	470
2285-HIN-2-ST-0608-144	6 3/8 x 8 1/2 x 2 1/8	Stacked	144	31 1/2 x 57 1/4 x 52 3/8	432

NOTE 1: These cabinets are also available without the heating unit and for other size trays. Consult factory.

NOTE 2: These cabinets are also available with left section non-heated (Ambient) and right section heated. Consult factory and see Options below.

NOTE 3: Style "B" cabinets are also available with vertical separators as shown on the picture on right hand side. See Options below. Aluminum construction is also available.

NOTE 4: Sample tray is required with order for proper sizing.

ADDITIONAL OPTIONS FOR CORRECTIONAL FACILITIES

1. Non-removable heating unit (in lieu of removable)
2. Heavy duty side/top mounted security lockable latch
3. 18 ga. s/s exterior
4. Extra set of hinges (3 sets in lieu of 2) for each door
5. 6" balloon casters (in lieu of std 6")
6. Left section ambient
7. Both sections ambient (non heated). Cabinet furnished without heating unit.
8. 8" polyurethane or 8" balloon casters
9. Vertical separators for STYLE "B"



STYLE "B"
2285-HIN-2-ST-910-112
(with optional vertical separators)

