

**Half size and under counter deluxe proofing non-insulated aluminum (except as noted)**

Furnished with PR-1600 proofing unit with 15 amps cord & NEMA 5-15P plug. 5" casters are standard. (except for under counter cabinets which use 3" casters). Power Requirements: Total 1675 watts on 110-120 volts. 60 hz, Single Phase, A.C.

**Deluxe Proofing Cabinets (For 18" x 26" sheet pans)**

Type	Size of Cabinet	Model Number	Pan Capacity (18"x26")	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)
					W	D	H	
Extruded Sides	Undercounter	9251-DEP-1810-UC	10	1½	22	30⅞	31⅞	128
	Half Size	9251-DEP-1818	18	1½	22	30⅞	45⅞	150
Angle Ledge	Undercounter	9281-DEP-1805-UC	5	3	22	30⅞	31⅞	120
	Half Size	9281-DEP-1809	9	3	22	30⅞	45⅞	150



9251-DEP-1818

**Deluxe Proofing Cabinets (For 23" x 23" donut screens)**

Type	Size of Cabinet	Model Number	*Pan Capacity (23"x23")	*Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)
					W	D	H	
Extruded Sides	Under counter	9251-DEP-2305-UC	5	3	27	30⅞	31⅞	155
	Half Size	9251-DEP-2307	7	3	27	30⅞	39⅞	165
	Full Size	9251-DEP-2317	17	3	27	30⅞	69⅞	180

\* Slides are spaced on 1½" centers but the capacity is shown based on wire screens spaced on 3" centers.



9251-DEP-2305-UC

**Delux Proofing Cabinets (Universal Angle Slide Type)**

Type	Model Number	Pan Size (Inches)	Pan Capacity	Pan Spacing (Inches)	O.A. Dimensions (Inches)			Weight (Pounds)
					W	D	H	
Undercounter	9231-DEP-UA-5-UC	Note 2	5 (Note 1)	3	29½	33⅞	31⅞	245
Half Size	9231-DEP-UA-6	Note 2	6 (Note 1)	3	29½	33⅞	39	195
	9231-DEP-UA-8	Note 2	8 (Note 1)	3	29½	33⅞	45	195

NOTE 1: Capacity shown is based on 3" spacing. Slides are adjustable on 1½" centers.

NOTE 2: Each pair of slides can accommodate on 18"x 26" bun pan or one GN2/1 gastronorm pan or two 14"x 18" trays or one 23"x 23" screen or two 12"x 20" steam pans or two gastronorm GN1/1 pans.

NOTE: LEXAN® door is standard on all of these proofing cabinets. Solid door in lieu of LEXAN® door is available at no extra charge. These are also available in S/S construction. Replace first number "9" by number "2" in model number. Consult factory.

NOTE: All of these proofing cabinets are also available as heating & holding cabinets at no extra charge. Replace "-DEP" by "-H" in model number. These are also available as Hot/Proof combination cabinets. Replace "-DEP" by "-HP" in model number at extra charge. These will be furnished with 20 amp cord & 5-20P plug. For other options, see catalog page C-1



9231-DEP-UA-8