



Hot cabinets, non-insulated, aluminum & stainless steel

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard.
 Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

CATALOG PAGES C-5 & C-6

Aluminum Hot Non-Insulated Cabinets

Type	Model Number	Pan Size (Inches)	Pan Spacing (Inches)	Pan Capacity	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
					W	D	H		
Extruded Side Panel	9250-H-1834	18 x 26	1½	34	22	30¾	69¾	168	\$3,119
	9250-H-1826	18 x 26	1½	26	22	30¾	57¾	160	3,338
	9250-H-1818	18 x 26	1½	18	22	30¾	45¾	148	3,217
Corrugated Sides	9270-H-1834	18 x 26	1½	34	22	30¾	69¾	166	3,653
Angle Ledge	9280-H-1817	18 x 26	3	17	22	30¾	69¾	165	3,501
	9280-H-1813	18 x 26	3	13	22	30¾	57¾	154	3,523
	9280-H-1809	18 x 26	3	9	22	30¾	45¾	142	3,369
	9280-H-1434	14 x 18	3	34	22	32¾	69¾	178	3,860



9250-H-1834

Stainless Steel Hot Non-Insulated Cabinets

Type of Slide	Model Number	Pan Size (Inches)	Pan Spacing (Inches)	Pan Capacity	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
					W	D	H		
Corrugated	2270-H-1834	1½	18 x 26	34	22	30¾	69¾	265	\$5,261
Channel	2250-H-1834	1½	18 x 26	34	22	30¾	69¾	255	5,493
Angle Ledge	2280-H-1817	3	18 x 26	17	22	30¾	69¾	240	5,340
	2280-H-1434	3	14 x 18	34	22	32¾	69¾	252	5,768



9270-H-1834

NOTE: Angle ledge cabinets are also available in spacing other than 3". Consult factory.
 For options, see Table CC-1

Hot cabinets, insulated, aluminum & stainless steel

Furnished with HE-2000 heating unit with 20 amps cord & NEMA 5-20P plug. 5" casters are standard.
 Power Requirements: Total 2075 watts on 110-120 volts. 60 hz, Single Phase, A.C.

CATALOG PAGES C-5 & C-6

Aluminum Hot Insulated Cabinets (Removable Racks) (see notes 1 & 2)

Type	Model Number	Pan Size (Inches)	Pan Spacing (Inches)	Pan Capacity	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
					W	D	H		
Extruded Side Channels	*9252-HIN-DD-1834	18 x 26	1½	34	27	36¾	72½	265	\$4,621
	9252-HIN-1826	18 x 26	1½	26	27	36¾	60½	237	4,352
Angle Ledge	*9282-HIN-DD-1817	18 x 26	3	17	27	36¾	72½	255	4,824
	9282-HIN-1813	18 x 26	3	13	27	36¾	60½	230	4,126
	*9282-HIN-DD-1434	14 x 18	3	34	27	36¾	72½	255	5,051
	9282-HIN-1426	14 x 18	3	26	27	36¾	60½	230	4,849



9252-HIN-DD-1834
 (with optional push handles)

Stainless Steel Hot Insulated Cabinets (Removable Racks) (see notes 1 & 2)

Type	Model Number	Pan Size (Inches)	Pan Spacing (Inches)	Pan Capacity	O.A. Dimensions (Inches)			Weight (Pounds)	List Price
					W	D	H		
Channel Slide	*2252-HIN-DD-1834	18 x 26	1½	34	27	36¾	72½	378	\$7,072
	2252-HIN-1826	18 x 26	1½	26	27	36¾	60½	360	6,368
Angle Ledge	*2282-HIN-DD-1817	18 x 26	3	17	27	36¾	72½	380	7,198
	2282-HIN-1813	18 x 26	3	13	27	36¾	60½	360	6,491
	*2282-HIN-DD-1434	14 x 18	3	34	27	36¾	72½	386	7,366
	2282-HIN-1426	14 x 18	3	26	27	36¾	60½	364	6,612

*Dutch doors are standard on these 72½" tall hot insulated cabinets. These are also available with single door.
 Deduct \$ 102 and delete "DD" in the model number.

NOTE 1. These hot insulated cabinets are also available as "proof" only cabinets at no extra charge. Replace the letters "HIN" in the model number by letters "PIN". For hot/proof combination cabinets, see page PC-5. For other options, see, Table CC-1. Angle ledge cabinets are also available with spacing other than 3". Consult factory.

NOTE 2. Hot insulated cabinets can also be furnished with 1600w heating unit (HE-1600) for 15 amps service instead of standard 2000w heating unit (HE-2000) at no extra charge. Consult factory.



TABLE CC-1
OPTIONS FOR PROOFER & HOT CABINETS

Table with 3 columns: Item Description, ALUMINUM MODELS, and STAINLESS STEEL MODEL. Lists 31 items such as corner bumpers, casters, and heating units with their respective prices.

*FOR HOT INSULATED CABINETS WITH TOP MOUNTED HEATING UNITS ONLY.

NOTE: Most aluminum hot, proof & hot/proof cabinets are also available in s/s construction. Add 65% to list prices of aluminum models unless listed otherwise based on a minimum quantity of 5 units & an up charge of 20% to 80% may apply for quantities under 5. Consult factory.